



**Eco-Smart, Inc.**

TOLL FREE: (888)329-2705 FAX: (941)377-9460 info@eco-smart.com

## Solar Air Conditioning - Wall Mount

### Wall Mount Specifications

MODEL	INDOOR UNIT		SWM 125P	SWM 185P	SWM 245P
	OUTDOOR UNIT		SP12C	SP18C	SP24C
NOMINAL COOLING CAPACITY	Btu/h		12,000	18,000	24,000
	W		3,516	5,274	7,032
	Kcal/h		3,024	4,536	6,048
RATED TOTAL POWER CONSUMPTION	W		818	1,113	1760
RATED TOTAL RUNNING CURRENT	A		3.72	5.06	8
ENERGY EFFICIENCY RATING (EER)			14.66	16.17	13.63
REFRIGERANT/CONTROL			R407C		
INDOOR					
POWER SOURCE	V/Ph/Hz		240/1/50-60		
FAN	AIR FLOW	cfm/cmm	355/10.06	510/14.45	650/18.42
	RATED INPUT POWER	W	30	50	69
	RATED RUNNING CURRENT	A	0.13	0.22	0.29
DIMENSION	HEIGHT	mm/in	260/10.2	306/12.0	306/12.0
	WIDTH	mm/in	899/35.4	1,062/41.8	1,062/41.8
	DEPTH	mm/in	198/7.80	222/8.7	222/8.7
WEIGHT	kg		9.4	15	15
SOUND PRESSURE LEVEL - H/M/L	dba		42/36/29	43/40/35	49/44/42
CONTROL	ROOM TEMPERATURE		THERMOSTAT CONTROL		
	AIR DISCHARGE		AUTO LOUVER (UP & DOWN) & MANUAL ADJUST GRILLE (LEFT & RIGHT)		
	OPERATION		LCD REMOTE CONTROL		
CONDENSATE DRAIN SIZE	mm/in		16.0/0.63	20.0/0.79	
AIR FILTER			WASHABLE ANTI FUNGUS SARANE FILTER		

### Notes:

1. Specifications are subject to change by the Manufacturer without prior notice.
  2. Nominal Cooling Capacity is based on the following conditions: Cooling 27° DB/19° WB Indoor and 35° CB outdoor
  3. Sound pressure level is tested according to J13 D 3015 Measurement point is 1.0m in Front and 0.3m below the unit.
- \*Available in wireless models only.