



Silicate dispersion primer

Technical sheet

Fields of application:

- for the solidification and the regulation of the absorptive capacity of mineral board board as used in Mold Preventing Interior System components and Insulating board.

Properties:

- high solidification
- allows water damp diffusion
- odorless
- regulation of the absorptive capacity by crystallization
- high alkalinity

Technical data:

Material	Binding material potassium silicate, acrylic resin dispersion
Specific weight	approx. 1,1 g/m ³

Processing directions:

Pre-treatment of the surface:

The surface must be free of residuals (acid salts, bitumen, coatings, oil and the like). Protect window sills, mounted parts, glass, ceramic, clinker, natural stone, coated and anodized surfaces from penetration by masking them.

Processing:

Apply Primer approx. 0.60 - 1.25 oz per ft² undiluted by spraying, brushing or with a paint roller.

Processing temperature:

The surface and ambient temperatures should not drop under +8°C.

Drying time:

Approx. 2 - 4 hours depending on temperature and humidity.

Cleaning:

Clean the tools with water immediately after use.

The data contained in this document are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions or technical data etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. All former technical leaflets are replaced by this one.



Silicate dispersion primer

Technical sheet

Packing units:

Primer PP-Container with 1.3 gallon
 PP-Container with 2.6 gallon

Safety advices:

S2: Keep out of the reach of children
S23: Do not breathe vapour/spray
S24/25: Avoid contact with skin and eyes
S29: Do not empty into drains

Storage:

In original packaging cool, frost-free storable for at least 6 months.

Maintenance of industrial health and safety standards:

Please regard regulations issued by local professional associations.

Material Safety Data Sheet:

We provide the Material Safety Data Sheet on demand.

The data contained in this document are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions or technical data etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. All former technical leaflets are replaced by this one.